



MCM

## display

pointer  
unit  
accuracy class referred to the full-scale value

black conform to DIN 43802 – scale plate division 90°  
A  
1,5

## input

burden ammeter

$\mu$ A : 100 | 150 | 250 | 400 | 600  
mA: 1 | 1,5 | 2,5 | 4 | 5 | 6 | 10 | 15 | 20 | 25 | 40 | 60 | 100 | 150 |  
250 | 400 | 500 | 600 | 4-20mA  
A : 1 | 1,5 | 2,5 | 4 | 5 | 6 | 10 | 15 | 20 | 25 | 30  
With Shunt .../60mV DC oder .../150mV DC  
60mV

## standards

CEI EN610 10-1 CEI EN 60051-1-2

## Environmental conditions

reference temperature  
operating temperature  
effect temperature  
storage temperature

20°C +/- 1°C  
20°C +/- 10°C (-10...+55°C without damage in continuous use)  
+/- 0,05% / °C  
-40....+70°C

## housing

front frame  
mounting  
depth of housing  
connection  
housing  
protection  
weight

52,5x 45mm  
din-rail 35mm  
58mm  
screws  
thermoplastic according to UL-94, V-0 classification  
IP 40  
ca. 0,12 kg

## connection / dimensions

